

Gear Protect

Description

High-pressure wear protection additive using the latest technology, designed for use in modern manual, auxiliary and differential transmissions. The transmission runs more quietly and easily, with smoother shifting. Smooths tooth faces and increases the load-bearing capacity. The product has a long-term effect.



Properties

- outstanding emergency-running properties
- friction and wear reducing
- increases smooth operation
- reduces gearshift resistance
- reduces transmission noise
- secures optimum transmission operation

legally binding.

Technical data

Base	synthetic additives/carrier oil
Density at 15 °C	0,94 g/cm ³ DIN 51757
Viscosity at 40 °C	80 mm ² /s DIN 51562
Flash point	>180 °C DIN ISO 2592
Pour point	-25 °C DIN ISO 3016
Color / appearance	green
Form	liquid

Areas of application

For manual, auxiliary and differential transmissions.
Not to be used in motorbikes or fully automatic transmissions and differential transmissions with limited slip differential.

Application

One 80 ml tube is sufficient for 2 liters of gear oil. Before adding, the corresponding amount of gear oil must be removed from the transmission using the tube provided and disposed of in accordance with the regulations. Single addition at any time, particularly during oil changes and repairs.

Note: Not suitable for use on motorbikes with wet clutches.

Available pack sizes

80 ml Tube plastic	1007
	DE-EN-ES-FR-IT-NL

Our information is based on thorough research and may be considered reliable, although not