

Top Tec 6200 0W-20

Description

High-tech low-friction motor oil based on synthetic technology. Developed for the high requirements of Audi, Porsche, Seat, Škoda and VW. The lower viscosity of the Longlife IV lubricant ensures excellent cold-start behavior and improves the engine efficiency. Offers an additional reduction of approx. 1.5 % in consumption compared with the already fuel-saving Longlife III. Innovative additive technology guarantees excellent protection against wear, impressive engine cleanliness and greater oxidation stability. Enables extremely long oil change intervals (WIV, etc.).

Properties

- tested for turbochargers and catalytic converters
- excellent wear resistance
- increases operational reliability
- excellent cold-start behavior
- outstanding resistance to oxidation
- optimum protection when using E10 fuel
- shortens the start time

Specifications / Approvals

ACEA C5 • Ford WSS-M2C 956-A1 • Porsche C20 • VW 508 00 • VW 509 00

Technical data

Viscosity SAE class	0W-20 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	44,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8,4 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	170 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D 5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	10,5 % CEC-L-40-A-93
Total base number	9,2 mg KOH/g DIN ISO 3771



Technical data

Flash point	220 °C DIN ISO 2592
Sulfate ash	≤ 0,8 % DIN 51575
Color / appearance	greenish
Oil base	Advanced Full Synthetic

Areas of application

For various vehicles from Audi, Porsche, Seat, Škoda and VW. Use only in gasoline and diesel engines with a particulate filter (e.g. TSI, TFSI, TDI) that require a lubricant of VW standard 508 00/509 00 or Porsche standard C20. Tested for turbochargers and catalytic converters. Not backwards compatible.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed.

Available pack sizes

1 l Canister plastic	20787 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	20788 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	20789 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	20782 DE-EN-ES-IT-PT
20 l Bag-in-Box	21960 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
60 l Black plate barrel	20783 DE-EN-ES-FR-IT-PT

Product information

PI 55/09/21/2026



Top Tec 6200 0W-20

Available pack sizes

205 l Black 20785
plate barrel DE-EN-ES-FR-IT-PT

**Our information is based on thorough research
and may be considered reliable, although not
legally binding.**