

Petrol Stabilizer

Description

Modern ash-free combination of agents with preservation and material protection properties. The product has been formulated using state-of-the-art additive and fuel technologies.

Properties

- tested for the use with catalytic converters
- has a lasting effect
- simple to use
- cost-effective due to exact dosage
- protects fuel against oxidation and aging

Technical data

Base	additive mixture in carrier liquid
Color / appearance	blue
Odor	characteristic
Form	liquid
Density at 15 °C	0,822 g/cm ³
Hazard class as per German VbF	A III
Flash point	>61 °C
Viscosity at 40 °C	<7 mm ² /s

Areas of application

Added to the fuel of all 2-stroke and 4-stroke gasoline engines. For decommissioning and preserving motorcycles, classic cars and engine-powered garden equipment, as well as gas-powered vehicles.

Application

25 ml (added by dosing device) is sufficient to preserve 5 litres of fuel. Before putting into storage, add the appropriate amount to the tank and run the engine for approx. 10 minutes.

Available pack sizes

250 ml Dispensing bottle plastic	5107 DE-FR-NL
250 ml Dispensing bottle plastic	21646 EN-ES-PT
1.000 l Container	21901 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

