

Valve Clean

Description

Cleans valves, injection systems, intakes, carburetors, combustion chambers, and prevents deposits. This ensures optimal engine operation and helps protect the engine under extreme operating conditions, such as city driving, short trips, and traffic jams. Tested for use with turbochargers and catalytic converters.

Properties

- good corrosion protection
- tested for turbochargers and catalytic converters
- reduces deposits

Technical data

Form	liquid
Color / appearance	yellow
Odor	characteristic
Density at 20 °C	0,816 g/ml
Flash point	>61 °C
Shelf life in original sealed container	60 months

Areas of application

For all gasoline engines (carburetors and engines with manifold fuel injection).

Application

Add to fuel whenever filling up. Contents sufficient to treat up to 75 liters of fuel.

Available pack sizes

150 ml Can sheet metal	1014 DE-FR-NL
150 ml Can sheet metal	2503 DE-ES-PT
150 ml Can sheet metal	2952 EL-EN-IT
150 ml Can sheet metal	8373 AR-EN-FR
150 ml Can sheet metal	20456 BG-DE-PL
150 ml Can sheet metal	21504 DE-FR
150 ml Can sheet metal	21621 CS-RO-SK

Our information is based on thorough research and may be considered reliable, although not legally binding.

