Product information
Speed Tec Gasoline

PI 51/08/18/2026



Description
State-of-the-art, ash-free fuel additive for improving combustion and acceleration in partial load range. Compatible with all gasoline and additive qualities. The acceleration of the vehicle is improved considerably.

Properties
- improves acceleration
- optimizes engine performance
- contains no organometallic compounds
- tested for the use with catalytic converters
- does not influence the octane number
- better drivability

Technical data

Base	Additive mixture in carrier fluid
Color / appearance	light brown
Density at 15 °C	0,825 g/cm³
Flash point	>63 °C
Odor	characteristic
Form	liquid
Viscosity at 40 °C	<7 mm²/s

Areas of application
Used as an additive in the fuel of all 2-stroke and 4-stroke gasoline engines, especially for motor vehicle engines. Can also be used in two-wheeled vehicles. For the improvement of vehicle acceleration and smooth operation.

Application
One 250 ml can is sufficient for max. 70 liters of fuel. Mix the contents of the can with the fuel. Mixing takes place automatically.

Available pack sizes

250 ml Can sheet metal	2848 DA-EN-FI-NO-SV
250 ml Can sheet metal	3720 DE-EN-IT
250 ml Can sheet metal	21644 DE-ES-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com